



400kg Hydraulic Track Loader

Features & Specifications

- Variable speed forward & reverse
- Stand on fold-up ride platform
- Centrifugal clutch steering
- Hydraulic lift & bucket tilt operations
- Heavy duty monoconstruction steel chassis
- Heavy duty 1 metre wide bucket
- Ground Clearance 150mm
- Heavy duty steel belted rubber tracks
- Optional attachments: Forks, Excavating bucket, Hydraulic Augers & more.
- Easy connect dry break hydraulic fittings
- LED Headlight
- 12V Electric Start
- Genuine Yanmar Engine
- Emission Standards EUR 5

Make & Model

Kusing SLM-T460V

Engine Make & Model

Yanmar 3TNV80F-SDWB

Engine Output & Displacement

17.8 KW / 1267cc Indirect Injection

Engine Type

3 Cylinder 4 Stroke Inline Diesel

Bore & Stroke

80 x 84 mm

Fuel Tank Capacity

10 Litres

Maximum Carry Weight

400kg

Rated Carry Weight

300kg

Maximum Lift Height to bucket pin

1.9 metres

Maximum Height Unloading Angle

34 Degrees

Operating Speed Capacity

0-6 km/hour

Fuel Consumption Est.

3.7 L/hr @ 2500RPM

Engine Oil Specification

15W/40

Engine Oil Capacity Est.

9 Litres

Hydraulic Oil Specification

ISO 46 Synthetic

Hydraulic operating pressure

17-21BAR

Noise Level

65DBA

Bucket Capacity

0.12m3

Bucket Dimensions

100W x 37H x 44D cm

Track Width

18cm

Dimensions

218L x 104W x 133H cm

Shipping Dimensions

120L x 106W x 145H cm

Weight

1200kg

Shipping Weight

1220kg